

Product Datasheet

Name - AURALIS METAL ENCLOSURE 8W

Catalogue number – AU77ZX1

Main -

Parameter	Description
Product Name	Metal Enclosure
Application	Distribution of single phase & neutral through SP MCBs
Range	Auralis
Operating Voltage / Frequency	240V AC / 50 Hz
Current rating	Up to 63A rated
Insulation voltage	500V AC
Impulse voltage	4 kV AC
Busbar	100A rated, Silver plated,
DB Colour / Finish	RAL 9003, powder coated, 60-90 microns, texture finish
Supplied components	Earth bar, Neutral bar, busbar, connecting cables, blank plate, labelling sticker

Complementary -

Parameter	Description
No. of 18mm modules	8
Number of Ways	8
Product Standard	Complies with IS / IEC 61439-3
Installation	Wall / Surface mounting
Product Architecture	Single door DBs – 3 piece – U-box, frame with centre plate, door
Ingress Protection (IP)	IP30
Impact resistance (IK)	IK09
DB door	Reversible, with electrical continuity
DB doorknob	With strong IP protection, endurance life, easy operation & with label holder
DB raw material	Galvanized iron sheet (Zinc coated GI)
Product Height	External - 150 mm
Product Width	External - 120 mm
Product Depth	External - 65 mm

Packing Unit 1 -

Parameter	Description
Type of packing 1	Carton
No of units packed	1 Piece
Package Height	External - 158 mm
Package Width	External – 201 mm
Package Depth	External - 76 mm

Packing Unit 2 -

Parameter	Description
Type of packing 1	Carton
No of units packed	12 Piece
Package Height	External - 340 mm
Package Width	External - 425 mm

Package Depth	External - 255 mm
---------------	-------------------

Warrantee – 24 months