

Product Datasheet

Name - AURALIS FLEXI TIER 3 ROW 14 MODULE DD DB

Catalogue number – AU88ZX1

Main -

Parameter	Description
Product Name	Flexi Tier Distribution board
Application	Distribution of three phase & neutral through any required combination of incoming and outgoing devices in SP/DP/TP/FP MCBs -Can be converted to PPI DBs by using suitable PPI Kit
Range	Auralis
Operating Voltage / Frequency	415 AC / 50 Hz
Current rating	Up to 63A rated
Insulation voltage	500V AC
Impulse voltage	4 kV AC
Busbar	100A rated, Silver plated,
DB Colour / Finish	RAL 9003, powder coated, 60-90 microns, texture finish
Supplied components	Earth bar, Neutral bar, busbar, connecting cables, blank plate, labelling sticker

Complementary -

Parameter	Description
No. of 18mm modules	14
Product Standard	Complies with IS / IEC 61439-3
Installation	Wall / Surface mounting
Product Architecture	Double door DBs – 4 piece – U-box, frame, centre plate, door
Ingress Protection (IP)	IP43
Impact resistance (IK)	IK09
DB door	Reversible, with electrical continuity
DB doorknob	With strong IP protection, endurance life, easy operation & with label holder
DB raw material	Galvanized iron sheet (Zinc coated GI)
Product Height	External - 550 mm
Product Width	External – 450 mm
Product Depth	External - 99 mm

Packing Unit -

Parameter	Description
No of units packed	1 Piece
Package Height	External - 575 mm
Package Width	External - 475 mm
Package Depth	External - 162 mm

Warranty – 24 months