

Product Datasheet

Name – AURALIS COMMUNICATION ONT DB

Catalogue number – AU86ZX1

Main -

Parameter	Description
Product Name	AURALIS COMMUNICATION ONT DB
Application	central point for internet signal distribution received through of Optical Fiber network, interference free signal receiving and routing of signal
Range	Auralis
Operating Voltage / Frequency	240V AC / 50 Hz
Current rating	Up to 63A rated
Insulation voltage	500V AC
Impulse voltage	4 kV AC
Busbar	100A rated, Silver plated,
DB Colour / Finish	RAL 9003, powder coated, 60-90 microns, texture finish
Supplied components	Earth bar, Neutral bar, busbar, connecting cables, blank plate, labelling sticker

Complementary -

Parameter	Description
Product Standard	Complies with IS / IEC 61439-3
Operating Voltage / Frequency	240V AC / 50 Hz
Current rating	Up to 63A rated
Insulation voltage	500V AC
Impulse voltage	4 kV AC
Installation	Wall / Surface mounting
Product Architecture	Double door DB – 4 piece – U-box, frame, centre plate, door
Ingress Protection (IP)	IP43
Impact resistance (IK)	IK08
DB door	Split and Reversible, with electrical continuity
DB doorknob	With strong IP protection, endurance life, easy operation & with label holder
DB raw material	Galvanized iron sheet (Zinc coated GI)
Product Height	External - 350 mm
Product Width	External - 375 mm
Product Depth	External - 94 mm

Packing Unit -

Parameter	Description
No of units packed	1 Piece
Package Height	External - 400 mm
Package Width	External - 475 mm
Package Depth	External - 162 mm

Warranty – 24 months