

Product Datasheet

Name - Auralis Phase Selector Switch DB 6W

Catalogue No. - AV02ZX1

Parameter	Description
Product Name	6W Phase Selector switch Distribution board
Application	select appropriate available source of power from available phases
Range	Auralis
Phase selector switch	Led indicator light for RYB phase on switch allows easy identification of fault and phase selection in case of single-phase fault in 3 phase supply
Operating Voltage / Frequency	240V AC / 50 Hz
Current rating	Up to 63A rated
Insulation voltage	500V AC
Impulse voltage	4 kV AC
Busbar	100A rated, Silver plated,
DB Colour / Finish	RAL 9003, powder coated, 60-90 microns, texture finish
Supplied components	Earth bar, Neutral bar, busbar, connecting cables, blank plate, labelling sticker

Complementary -

Parameter	Description
No. of 18mm modules	26
Number of Ways	6
Product Standard	Complies with IS / IEC 61439-3
Installation	Wall / Surface mounting
Product Architecture	Double door DB – 4 piece – U-box, frame, centre plate, door
Ingress Protection (IP)	IP43
Impact resistance (IK)	IK09
DB door	Split and reversible, with electrical continuity
DB doorknob	With strong IP protection, endurance life, easy operation & with label holder
Incomer / Outgoing protection devices	Incomer – 4P+4P RCCB / RCBO / Isolator Outgoing – 3x6 SP MCBs
DB raw material	Galvanized iron sheet (Zinc coated GI)
Product Height	External - 555 mm
Product Width	External - 486 mm
Product Depth	External - 131 mm

Packing Unit -

Parameter	Description
No of units packed	1 Piece
Package Height	External - 580 mm
Package Width	External - 506 mm
Package Depth	External - 200 mm

Warranty – 24 months