



RCCB 25A 4P 30mA AC Type
AX06ZU2

Main

Range	EL9
Product name	
Product or component type	Residual Current Circuit Breaker
Device Short name	RCCB
Poles description	4P
Neutral Position	Right
[In] Rated current	25 A
Network type	AC
Earth-leakage sensitivity	30mA
Earth-leakage protection time delay	
Earth-leakage protection class	Type AC
Rated breaking and making capacity	500 A
Suitability for isolation	

Complementary

Network frequency	
[Ue] rated operational voltage	415 V
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6kV
Contact position indicator	Yes
Control Type	Toggle
Local signalling	ON, OFF, fault trip
Mounting mode	Clip-on
Mounting support	DIN rail
Comb busbar and distribution Block capability	
Connection pitch	18 mm between phases
9mm pitches	
Height	81 mm
Width	72 mm
Depth	82 mm

Product weight	328 g
Colour	
Mechanical durability	≥2000
Electrical durability	≥2000
Locking options description	
Connections – terminals	
Wire stripping length	12 mm
Tightening torque	2.5 N.m

Environment

Standards	IS:1260-1/IEC/EN61008-1
Product certifications	ISI
IP degree of protection	IP20
Pollution degree	2
Tropicalisation	
Relative humidity	
Ambient air temperature for operation	-25°C to 55°C
Ambient air temperature for storage	-40°C to 70°C

Packing Units

Unit Type of Package 1	
Number of Units in Package 1	1
Package 1 Height	78 mm
Package 1 Width	75 mm
Package 1 Length	89 mm
Package 1 Weight	349 g
Unit Type of Package 2	
Number of Units in Package 2	3
Package 2 Height	93 mm
Package 2 Width	84 mm
Package 2 Length	235 mm
Package 2 Weight	1.14 kg
Unit Type of Package 3	
Number of Units in Package 3	30
Package 3 Height	242 mm
Package 3 Width	183 mm
Package 3 Length	488 mm
Package 3 Weight	11.66 kg

Contractual warranty

Warranty (in months)	24 Months
----------------------	-----------